

Scopus

Document details

[< Back to results](#) | 1 of 2 [Next >](#)[Export](#) [Download](#) [Print](#) [E-mail](#) [Save to PDF](#) [Add to List](#) [More... >](#)[Full Text](#)[View at Publisher](#)

Applied Mechanics and Materials

Volume 606, 2014, Pages 113-117

1st International Materials, Industrial and Manufacturing Engineering Conference, MIMEC 2013; Johor Bahru; Malaysia; 4 December 2013 through 6 December 2013; Code 107118

Parameter study of tool-laminate interface through simulation for composite manufacturing using autoclave process (Conference Paper)

Mezeix, L.^a [✉](#), Nasir, M.N.M.^a [✉](#), Aminanda, Y.^a [✉](#), Rivai, A.^b [✉](#), Ali, K.M.^c [✉](#)^aInternational Islamic University Malaysia, Kuala Lumpur, Malaysia^bUniversiti Teknikal Malaysia Melaka, Melaka, Malaysia^cAerospace Malaysia Innovation Center, TO2, 3rd floor 2310, Century Square, Jalan Usahawan, 63000 Cyberjaya, Selangor, Malaysia

Abstract

[View references \(9\)](#)

Modeling the spring-back requires tool-laminate interaction to be taken into account. In this study, an interface based on orthotropic linear behavior coupled with an out - of - plane shear stress failure was proposed to simulate the tool-laminate interaction. The results from this particular model captured the out - of - plane shear stress distribution. The model allows predicting the warpage displacement in function of interface properties; shear modulus and shear stress failure which leads to the construction of Chart Design. Additionally, the influence of the number of plies was studied as well and the evolution of the maximum warpage agreed with the literature. © (2014) Trans Tech Publications, Switzerland.

Author keywords

CFRP Composite manufacturing Springback Tool - part interaction

Indexed keywords

Engineering controlled terms: Carbon fiber reinforced plastics Industrial research Manufacture Shear stress

Autoclave process

Composite manufacturing

Interface property

Linear behavior

Out - of - plane shear

Parameter studies

Spring-back

Tool - part interaction

Metrics [View all metrics >](#)

3 Citations in Scopus

75th Percentile

5.42 Field-Weighted Citation Impact



PlumX Metrics

Usage, Captures, Mentions, Social Media and Citations beyond Scopus.

Cited by 3 documents

Spring-in prediction for carbon/epoxy aerospace composite structure

Fiorina, M. , Seman, A. , Castanie, B. (2017) *Composite Structures*

Spring-back simulation of unidirectional carbon/epoxy L-shaped laminate composites manufactured through autoclave processing

Nasir, M.N.M. , Mezeix, L. , Aminanda, Y. (2016) *IOP Conference Series: Materials Science and Engineering*

Spring-back simulation of unidirectional carbon/epoxy flat laminate composite manufactured through autoclave process

Mezeix, L. , Seman, A. , Nasir, M.N.M. (2015) *Composite Structures*[View all 3 citing documents](#)

Inform me when this document is cited in Scopus:

[Set citation alert >](#)[Set citation feed >](#)

Engineering main heading:

Laminated composites

ISSN: 16609336
ISBN: 978-303835183-2
Source Type: Book series
Original language: English

DOI: 10.4028/www.scientific.net/AMM.606.113
Document Type: Conference Paper
Sponsors:
Publisher: Trans Tech Publications Ltd

References (9)

[View in search results format >](#)

All

[Export](#)

Print



E-mail

[Save to PDF](#)[Create bibliography](#)

1 Olivier, P.A.

A note upon the development of residual curing strains in carbon/epoxy laminates. Study by thermomechanical analysis

(2006) *Composites Part A: Applied Science and Manufacturing*, 37 (4), pp. 602-616. Cited 26 times.
 doi: 10.1016/j.compositesa.2005.05.006

[View at Publisher](#)

2 Parlevliet, P.P., Bersee, H.E.N., Beukers, A.

Residual stresses in thermoplastic composites - a study of the literature. Part III: Effects of thermal residual stresses

(2007) *Composites Part A: Applied Science and Manufacturing*, 38 (6), pp. 1581-1596. Cited 92 times.
 doi: 10.1016/j.compositesa.2006.12.005

[View at Publisher](#)

3 Twigg, G., Poursartip, A., Fernlund, G.

An experimental method for quantifying tool-part shear interaction during composites processing

(2003) *Composites Science and Technology*, 63 (13), pp. 1985-2002. Cited 64 times.
 doi: 10.1016/S0266-3538(03)00172-6

[View at Publisher](#)

4 Nelson, Ron H., Cairns, Douglas S.

Prediction of dimensional changes in composite laminates during cure

(1989) *International SAMPE Symposium and Exhibition (Proceedings)*, 34 (pt2), pp. 2397-2410. Cited 61 times.



5 Ridgard, Christopher

Accuracy and distortion of composite parts and tools: Causes and solutions

(1993) *Technical Paper - Society of Manufacturing Engineers. EM*, pp. 1-18. Cited 3 times.



6 Twigg, G., Poursartip, A., Fernlund, G.

Tool-part interaction in composites processing

(2003) *Part I: Experimental investigation and analytical model, Compos Part A*, 35, pp. 121-133. Cited 4 times.

Related documents

Tool-part interaction in composites processing. Part II: Numerical modelling

Twigg, G. , Poursartip, A. , Fernlund, G.

(2004) *Composites Part A: Applied Science and Manufacturing*

Investigation of tool-part interaction during autoclave processing of polymer composites structures

Kaushik, V. , Zeng, X. , Hendrickson, L.

(2005) *International SAMPE Symposium and Exhibition (Proceedings)*

Tool-part interaction in composites processing. Part I: Experimental investigation and analytical model

Twigg, G. , Poursartip, A. , Fernlund, G.

(2004) *Composites Part A: Applied Science and Manufacturing*

[View all related documents based on references](#)

[Find more related documents in Scopus based on:](#)

[Authors >](#) [Keywords >](#)

-
- ☐ 7 Clifford, S., Jansson, N., Yu, W., Michaud, V., Manson, J.-A.
Thermoviscoelastic anisotropic analysis of process induced residual stresses and dimensional stability in real polymer matrix composite components
(2006) *Composites Part A: Applied Science and Manufacturing*, 37 (4), pp. 538-545. Cited 27 times.
doi: 10.1016/j.compositesa.2005.05.008
[View at Publisher](#)
-
- ☐ 8 Fernlund, G., Rahman, N., Courdji, R., Bresslauer, M., Poursartip, A., Willden, K., Nelson, K.
Experimental and numerical study of the effect of cure cycle, tool surface, geometry, and lay-up on the dimensional fidelity of autoclave-processed composite parts
(2002) *Composites - Part A: Applied Science and Manufacturing*, 33 (3), pp. 341-351. Cited 134 times.
doi: 10.1016/S1359-835X(01)00123-3
[View at Publisher](#)
-
- ☐ 9 Twigg, G., Poursartip, A., Fernlund, G.
Tool-part interaction in composites processing
(2003) *Part II: Numerical Modeling, Compos Part A*, 35, pp. 135-141.
-

© Copyright 2014 Elsevier B.V., All rights reserved.

[Back to results](#) | 1 of 2 [Next >](#)

[Top of page](#)

About Scopus

[What is Scopus](#)
[Content coverage](#)
[Scopus blog](#)
[Scopus API](#)
[Privacy matters](#)

Language

[日本語に切り替える](#)
[切换到简体中文](#)
[切换到繁體中文](#)
[Русский язык](#)

Customer Service

[Help](#)
[Contact us](#)

ELSEVIER

[Terms and conditions](#) [Privacy policy](#)

Copyright © 2017 Elsevier B.V. All rights reserved. Scopus® is a registered trademark of Elsevier B.V.

Cookies are set by this site. To decline them or learn more, visit our [Cookies page](#).

RELX Gr